

RemoteMic[™] 3CP

Product Specification

Updated: 7/26/2024

 SC
 Sound Control Technologies
 Transmitter Module www.soundcontrol.net

 Mic In 1
 Mic In 2
 Mic In 3

 SC
 Sound Control Mic In 1
 Mic In 2

 Mic In 3
 RM-3CP-RXTM Receiver Module www.soundcontrol.net

 Mic Out 1
 Mic Out 2

 Mic Out 3
 Mic Out 3

The RM-3CP[™] kit provides a reliable transparent audio link between the table microphones and the connected Cisco Codec.

By simplifying complex cabling and extending traditional distance limitations up to 100m, SCT's extension kit provides integrators with cost and time saving solutions.

KEY FEATURES

- Extends up to 3 Cisco Table Microphones over a standard CAT5e/CAT6 cable up to 100m.
- Simple Plug & Play installation, no programming required.
- All hardware-specific codec connection cables are included.
- PowerSniffer included for testing SCTLink[™] cable conductor continuity.
- Integrator only required to provide a CAT5e/CAT6 SCTLink[™] Cable.

TECHNICAL SPECS

- Microphone Support: Up to 3 Cisco Microphone 20 or Microphone Table-J microphones.
- Cisco Microphone 60 and Microphone Table-E microphones supported with optional SCT RM-PRO[™] adapters.

SCTLINK[™] CABLE SPECS

SCT recommends CAT6 or better cable for the SCTLink[™]. The use of a shielded cable, while not required for most platforms, is highly recommended.

Proper termination and testing, along with good cable management, minimizes potential problems.

Wiring Termination Standard T568A or T568B 10m Minimum - 100m Maximum Length

Power Consumption A linked kit will consume 4.5W.

MODULE & POWER SUPPLY SPECS

RM-3CP[™] Transmitter Module

- Imperial Dims: H: 0.88" x W: 5.09" x D: 3.63"
- Metric Dims: H: 22mm x W: 129mm x D: 92mm
- Weight: 0.4 lbs / 168g

RM-3CP[™] Receiver Module

- Imperial Dims: H: 0.88" x W: 5.09" x D: 3.63"
- Metric Dims: H: 22mm x W: 129mm x D: 92mm
- Weight: 0.4 lbs / 168g

WPS-12[™] Power Supply (Included)

- Imperial Dims: H: 1.19" x W: 1.85" x D: 4.65"
- Metric Dims: H: 30mm x W: 47mm x D: 118mm
- Weight: 0.5 lbs / 236g
- Input: 100 to 240VAC, 47-63Hz, 1.45A Max
- Output: 30VDC, 2A Max
- Output Connector: 5.5mm x 2.5mm DC Plug
- Regulatory Approvals:

UL, CE, FCC, CCC, TÜV, RCM+GEMS, LPS, BIS, PSE, CB, DOE VI, CoC V5 & RoHS2

SUPPORTED DEVICES

https://www.soundcontrol.net/products/ camera-extension-kits/rm-3cp

Cisco Codec Plus, Codec Pro, Codec EQ, Room 55, Room 55 Dual, Room 70 G1, Room 70 G2, Room Kit Plus, Room Kit Pro, Room Kit and SX80 codecs.

Got questions? We've got answers. Check out our **FAQ's**!

PRODUCT WARRANTIES

www.soundcontrol.net/support

Included: 3 Year Standard Available: 2 Year Extended Advance Replacement Limited Warranty

Advance Replacement Limited Warranty





SOLUTION FINDER

Not sure where to start? Try our Solution Finder! www.soundcontrol.net/solution-finder

BUILT IN AMERICA

